

America West Drilling Supply

LXQ IR360 Shank



Hammer Specifications

Length (w/o drill bit)	48.7"
Outside Diameter	5.413"
Weight (w/o bit)	226.7 lbs.
Cylinder Bore	4.268
Piston O.D.	4.263"
Piston Stroke	4.527"
Piston Weight	45.8 lbs.
Hole Sizes	6" - 8"
Air Pressure Consumption	100 psi - 400 psi
Wrench Size	A/F 3.968"
Connection (API Reg Pin)	Std. 3 1/2"

Features:

- Easy to service
- Special heat-treated alloy piston for long life - Rockwell 60 Hardness
- Minimal performance loss when injecting foam or water
- Drills well underwater

1350 E. Glendale Avenue
Sparks, NV 89431
(800) 800-8444 | (775) 355-1199
Fax (775) 355-8775



www.awds.com

America West Drilling Supply



Missile LXQ
Series

Item #	Description	Part #
1	Back Head	LQ6001
2	Back Head O-Ring	LQ6002
3	Choke	
4	Air Check Valve	LQ6004
5	Air Check Valve Spring	LQ6005
6	Buffering Washer (Steel)	LQ6006
7	Make-Up Rubber (Buffering)	LQ6007
8	Air Distributor	LQ6008
9	Air Distributor O-Ring	LQ6009
10	Cylinder	LQR6010
11	Wear Sleeve	LQR6011
12	Piston	LQR6012
13	Piston Stop Ring	LQ6013
14	Bit Bearing O-Ring	LQR6014
15	Bit Bearing	LQR6015
16	Bit Retaining O-Ring	LQR6016
17	Bit Retainer	LQR6017
18	Chuck (Drive Sub)	LQR6018



LXQ IR360 Shank Hammer

Air Consumption Chart

PSI	150	200	250	300	350	400
CFM with blank choke	350	510	665	825	990	-
with 1/8" choke	385	570	735	915	1,090	-
with 1/4" choke	440	650	830	1,009	1,190	-

All hammers come fitted with a blank choke in the Air Check Valve.