

America West Drilling Supply

LXQ H150 Shank



Hammer Specifications

Length (w/o drill bit)	69.41"
Outside Diameter	12.6"
Weight (w/o bit)	1,878.12 lbs.
Cylinder Bore	9.449"
Piston O.D.	9.442"
Piston Stroke	4.92"
Piston Weight	338.19 lbs.
Hole Sizes	15" - 20"
Air Pressure Consumption	100 psi - 250 psi
Wrench Size	-
Connection (API Reg Pin)	Std. 8 5/8"

Features:

- Easy to service
- Special heat-treated alloy piston for long life - Rockwell 60 Hardness
- Minimal performance loss when injecting foam or water

1350 E. Glendale Avenue
Sparks, NV 89431
(800) 800-8444 | (775) 355-1199
Fax (775) 355-8775



www.awds.com

America West Drilling Supply

Missile LXQ Series



Item #	Description	Part #
1	Back Head	LQ1501H
2	Back Head O-Ring	LQ1502H
3	Back Head Washer	
4	Choke	LQ1504H
5	Air Check Valve	LQ1505H
6	Air Check Valve Spring	LQ1506H
7	Buffering Washer	LQ1507H
8	Buffering Ring	LQ1508H
9	Air Distributor	LQ1509H
10	Air Distributor O-Ring	LQ1510H
11	Cylinder	LQ1511H
12	Wear Sleeve	LQ1512H
13	Piston	LQ1513H
14	Piston Stop Ring	LQ1514H
15	Bit Retaining O-Ring	LQ1515H
16	Bit Retaining Ring	LQ1516H
17	Chuck Washer	LQ1517H
18	Chuck	LQ1518H
19	Drive Pin Set	LQ1519H
	Choke Plug Kit	LQ1529H
	O-Ring Kit	LQ1530H

LXQ H150 Shank Hammer

Air Consumption Chart

PSI	100	150	200	250	300	350
CFM with blank choke	800	1,100	1,650	2,110	-	-
with 1/8" choke	-	-	-	-	-	-
with 1/4" choke	-	-	-	-	-	-

All hammers come fitted with a blank choke in the Air Check Valve.