



5JW ROTATING HEAD



- Fluid Passage – 3" Maximum
- Compact Design
- Thrust Ball Bearings for pressure and radial load support
- Choice of hose and lower connection threads
- Easy field maintenance and repair
- Working Pressure to 2500 PSI

WEIGHTS AND DIMENSIONAL DATA

TYPE HEAD	WORKING PRES.	LENGTH INCHES	WT/LBS	LOWER CONN.* LH OR RH BOX OR PIN	HOSE CONN.	WATER COURSE
5JW	2500 PSI	17 1/2"	95	3" NPT or 4"	3" or 4"	3"

PARTS LIST

PART NUMBER	DESCRIPTION	WT/LBS	NUMBER REQ.	
5JW-2050-XX	WESTERN SWIVEL, 3" FEMALE HOSE CONNECTION STRAIGHT UP, WITH 3" NPT, RIGHT OR LEFT HAND, BOX OR PIN LOWER CONNECTION			
	ADD FOR SPECIAL LOWER CONNECTION			
	ADD FOR 4" HOSE CONNECTION			
5JW-04	GOOSENECK, 3" NPT FEMALE HOSE CONNECTION	25.00	1	
5JW-04A	GOOSENECK, 4" MALE HOSE CONNECTION	25.75	Option	
5JW-06	PACKING ADJUSTING GLAND	1.12	1	
5JW-06A	+ PACKING SEAT RING	.25	1	
5JW-06S	PACKING SEAT RING (STEEL)	1.00	Option	
5JW-07	+ HOUSING SEAL	.25	2	
5JW-07V	HOUSING SEAL VITON	.25	Option	
5JW-08	BEARING SPINDLE, 3" FLUID PASSAGE	8.00	1	
5JW-11	BEARING RETAINER WIRE	.10	1	
5JW-12	+ BEARING	8.00	2	
5JW-14	BEARING HOUSING	10.00	1	
5JW-16HA-RB	LOWER CONNECTION, 3" NPT RH BOX	15.00	Option	
5JW-16HA-RP	LOWER CONNECTION, 3" NPT RH PIN	14.00	Option	
5JW-16HA-LB	LOWER CONNECTION, 3" NPT LH BOX	15.00	1	
5JW-16HA-LP	LOWER CONNECTION, 3" NPT LH PIN	14.00	Option	
5JW-16IA-RB	LOWER CONNECTION, 4" NPT RH BOX	18.00	Option	
5JW-16IA-RP	LOWER CONNECTION, 4" NPT RH PIN	17.00	Option	
5JW-16IA-LB	LOWER CONNECTION, 4" NPT LH BOX	18.00	Option	
5JW-16IA-LP	LOWER CONNECTION, 4" NPT LH PIN	17.00	Option	
5JW-17	+ SPINDLE THREAD SEAL	.25	1	
5JW-20	+ PACKING SET	.50	1	
5JW-20-416	PACKING (LOW PRESSURE)	.50	Option	
5JW-21	LANTERN RING	1.00	1	
5JW-25	+ WASHPIPE	4.50	1	
OR-339	+ O RING	.01	1	
5JW-40R	REPAIR KIT + Included in Repair Kit			

Other sizes of connections available, please consult factory.

Option for above swivel, may affect pricing of complete swivel. Other options available, please consult factory.

